



# PANEL TYPE AIR CONDITIONERS

| Models                 | Unit         | PAC050.01                                  | PAC075.01   | PAC100.01   | PAC150.01   | PAC200.01    | PAC250.01    |
|------------------------|--------------|--|-------------|-------------|-------------|--------------|--------------|
| Cooling Capacity       | EN814 A35A35 | 500W                                       | 750W        | 1000W       | 1500W       | 2000W        | 2500W        |
| Cooling Capacity       | EN814 A35A50 | 400W                                       | 600W        | 800W        | 1200W       | 1600W        | 2000W        |
| Power Supply           | V / Hz       | 1 Phase 230V 50/60Hz                       |             |             |             |              |              |
| Dimensions HxWxD       | mm           | 500x310x205                                | 610x320x210 | 640x320x210 | 800x400x255 | 1000x255x400 | 1000x255x400 |
| Max. Current           | A            | 2.65/2.75                                  | 2.65/2.75   | 3.50/3.60   | 4.50/4.60   | 6.00         | 6.00         |
| Delayed fuse           | A            | 6  | 6           | 10          | 10          | 16           | 16           |
| Refrigerant            | -            | R134a                                      |             |             |             |              |              |
| Operating Temperature  | °C           | +20 / +55                                  |             |             |             |              |              |
| Temperature controller | -            | Digital thermostat factor, set 35 °C       |             |             |             |              |              |
| Compressor type        | -            | Hermetic                                   |             |             |             |              |              |
| Noise level            | dB(A)        | 52   | 56          | 62          | 65          | 70           | 70           |
| Electrical Connections | -            | 3-pole terminal connector                  |             |             |             |              |              |
| Protection Degree      | -            | Enclosure inside IP54, Ambient inside IP34 |             |             |             |              |              |
| Weight                 | kg           | 18.00                                      | 26.30       | 28.50       | 32.00       | 43.50        | 44.00        |
| Colour                 | -            | RAL7035 Grey, (INOX on request)            |             |             |             |              |              |
| Conformity             | -            | CE   |             |             |             |              |              |

